# WSLATE









**Dark** 









1"x6" Outside Corner

1"x6" Inside Corner



6"x6"





3"x6" Brick





1093581 - 12"x24"◆

2"x2" Mosaic (12"x12")







Light









1094155 1"x6" Outside Corner 1093652 1"x6" Inside Corner








1093650 6"x12" Cove Base

1093590 3"x6" Brick



1093586 2"x2" Mosaic (12"x12")







## Indigo







1"x6" Outside Corner





1"x6" Inside Corner



6"x6"





6"x12" Cove Base



3"x12" Bullnose

2"x2" Mosaic (12"x12")

1094271 - 12"x24"**◆** 

#### COLOR SPECIFICATIONS AND SIZES AVAILABLE

Nominal Size Dimension nominale	DARK	LIGHT	INDIGO	
18"x18"	1093579	1093578	1094272	
12"x24" ◆	1093581	1093580	1094271	
12"x12"	1093577	1093576	1094270	
6"x6"	1093585	1093584	1094274	
2"x2" Mosaic (12"x12")	1093587	1093586	1094276	
3"x6" Brick	1093591	1093590	1094273	
6"x12" Cove Base	1093651	1093650	1094277	
1"x6" Inside Corner	1094154	1093652	1094278	
1"x6" Outside Corner	1094156	1094155	1094279	
3"x12" Bullnose	1093583	1093582	1094275	

#### PACKAGING

NOMINAL SIZE	METRIC (CM)	THICKNESS (CM)	PIECES PER BOX	SQ. FT PER BOX	WEIGHT PER BOX	BOXES PER PALLET	WEIGHT PER PALLET
18"x18"	45x45	10 mm	6	13.5	32	432	1887
12"x24"	30x60	11 mm	6	12	48	576	2584
12"x12"	30x30	10 mm	13	13	48	624	2796
6"x6"	15x15	10 mm	30	7.5	72	540	1890
2"x2" Mosaic (12"x12")	30x30	10mm	10	10	45	450	1895
3"x6" Brick	7.5x15	10mm	40	5	58	290	1234
6"x12" Cove Base	15x30	8 mm	10	-	-	-	-
1"x6" Inside Corner	2.5x15	8 mm	4	-	-	-	-
1"x6" Outside Corner	2.5x15	8 mm	4	-	-	-	-
3"x12" Bullnose	7.5x30	10 mm	12	3	168	504	2184

ALL OTHER SIZES WILL BE PACKAGED AS ORDERED. PLEASE CONTACT FLORIM CUSTOMER SERVICE AT 877-FLORIM1 FOR PACKAGING INFORMATION.

♦ MINIMUM GROUT SIZE RECOMMENDED = 5 MM (OR APPROX. 3/16" IF STAGGERED TILE PLACEMENT, WE RECOMMEND USING A 30% OFFSET. IF SPECIFIED BRICK PATTERN WITH 1/2 PATTERN MANDATORY, A BIGGER GROUT IS RECOMMENDED TO HIDE IMPERFECTIONS OF INSTALLATION (MINIMUM 1/4").

#### SHADE VARIATION



#### **UNIFORM APPEARANCE**

Differences among pieces from the same production run are minimal.



### SLIGHT VARIATION

Clearly distinguishable differences in texture and/or pattern with similar colors.



#### MODERATE VARIATION

While the colors present on a single piece of tile will be indicative of the colors to be expected on the other tiles, the amount of colors on each piece will vary significantly.



#### SUBSTANTIAL VARIATION

Random color differences from tile to tile, so that one tile may have totally different colors from that on other tiles. Thus, the final installation will be unique.

TECHNICAL SPECIFICATIONS			
Surface Abrasion	PEI	IV	ASTM C1027
Water Absorption		≤ 0.5%	ASTM C373
Chemical Resistance		CLASS A	ASTM 650
O#i-i of Eristian	(Dry)	≥ 0.70 ♦	ASTM C1028
Coefficient of Friction	(Wet)	≥ 0.60 ◆	ASTM C1028
Stain Resistance		CLASS A	ASTM C1378
Breaking Strength		≥ 400	ASTM C648
Resistance to freeze		RESISTANT	ASTM C1026
Scratch Hardness		8	MOHS

ALL FLORIM USA PRODUCTS MEET OR EXCEED ALL STANDARDS IN ANSI A137.1.

♦ DUE TO THE INHERENT NATURE OF FIRED PORCELAIN TILE, IT IS IMPORTANT TO NOTE THAT THE COEFFICENT OF FRICTION MAY VARY WITHIN AND BETWEEN PRODUCT RUNS.

#### WHY PORCELAIN?

There are many reasons to choose impervious porcelain tile over other floor coverings. It offers the largest array of design options and holds its value the longest. In a comparison between the many different flooring options, porcelain tile offers one of the most durable and least expensive options over the lifespan of the building.

#### Benefits of Porcelain Tile

- Impervious to water
- Easy to maintain
- Variety of design optionsEnvironmentally friendly
- Resistant to germs and bacteria
- Fade resistant
- Fire resistant
- Durable best long-term value vs. other floor coverings

#### **HOW TO MAINTAIN YOUR PORCELAIN TILE**

- Sweep or vacuum regularly.
- Wash with a household cleaner and hot water then rinse with clean water (do not use wax, oil-based, or abrasive cleaners).

Find more care, maintenance, and installation tips at www.florim.com

Colors Shown in this brochure may vary from actual product. Final selection should be made from actual product samples.

















#### PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY

As a active member of the U.S Green Building Council, Florim spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices. Using Florim products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification (Leadership in Energy and Environmental Design).

A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE
Florim offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S.







#### PROGRESS THAT TOUCHES AND INVESTS IN THE ENTIRE SOCIETY

As a active member of the U.S Green Building Council, Florim spreads awareness to the entire American communities and encourages towards the use of building solutions inspired by environmentally friendly practices.

Using Florim products for project implementation, will positively contribute in obtaining scores and points required for earning the LEED certification (leadership in Energy and Environmental Design).

#### A COMMITMENT TO THE DEVELOPMENT OF PRODUCTS FOR A CONSCIOUS BUILDING TRADE

Florim offers products containing recycled material. The adoption of eco-compatible production systems is merit of Italian designs produced in the U.S

#### TECHNICAL DEVELOPMENT THAT CONSIDERS THE NATURAL ENVIRONMENT

Florim commits to the eco-compatible project and translates the same into an avant-guard production process



300 International Blvd. Clarksville, TN 37040 toll free 877 - Florim1 (356-7461) tel. 931 645 5100 www.florimusa.com

