

Product Specifications

Classification	ASTM F 1700 Class III Type B
Construction	Heterogeneous - Layered product consisting of wearlayer, decorative film, and backing with pre- and post-consumer content
Total Thickness	.120" (3.0 mm)
Wear Layer Thickness	32 mil (.032")
Emboss	Standard: Fresco (FC), Frost (FR), Pathway (PH), Quarry (QU) <i>Standard emboss varies by product.</i> <i>Other emboss designs available upon request.</i>
Edge Treatment	Square Edge (SE) or Slight Bevel (SB)
Products	45



Environmental Attributes

Reclamation	100% recyclable in the ReStart® Program
Indoor Air Quality	Meets CDPH 01350; FloorScore® Certified
Third Party Certification NSF-332	Gold

Performance Testing

Flexibility	ASTM F 137	Passes
Dimensional Stability	ASTM 2199	Passes
Residual Indentation	ASTM F 970 & ASTM F 1914	Excellent
Flammability	ASTM E 648	Class 1 CRF>0.45
Slip Resistance	ASTM C 1028* ASTM D 2047 ADA Compliant	Very Good (*textures) Passes FTC Slip Resistant Classified Product
Smoke Density	ASTM E 662	<450; Good
Abrasion	ASTM D 3884	Excellent
Castor Chair Suitability	ITTS 205	Very Good
Color Fastness	ASTM F 1515	Very Good
Chemical Resistance	ASTM F 925	Excellent

Warranty Information

20 year Commercial Limited Wear Warranty and Lifetime Residential Limited Wear Warranty

Installation Methods

Quarter Turn or Unidirectional

(For best design appeal and results, Tandus Centiva recommends the Quarter Turn installation method.)



QUARTER TURN



UNIDIRECTIONAL

Adhesive – CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose), CENTI 2000 EP (Epoxy) or other Tandus Centiva LVT recommended adhesives.

Sizes Available

- 12" x 12"
- 12" x 18"
- 12" x 36"
- 18" x 18"
- 18" x 36"
- 36" x 36"
- 4" x 36"
- 6" x 36"

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.
- Limited warranty and maintenance information for Tandus Centiva LVT may be found at www.tandus-centiva.com or by dialing 800.248.2878