


Product Specifications

Classification	ASTM F 1700 Class III Type B
Construction	Heterogeneous - Layered product consisting of wearlayer, decorative film, and backing with pre- and post-consumer content
Total Thickness	.120" (3.0 mm)
Wear Layer Thickness	20 mil (.020")
Finish	Polyurethane reinforced
Emboss	Standard: Linear Wood (LW), Cross Grain (CG), Weathered Grain (WG) <i>Standard emboss varies by product.</i>
Edge Treatment	Square Edge (SE)
Products	25



Environmental Attributes

Reclamation	100% recyclable in the ReStart® Program
Indoor Air Quality	Meets CDPH 01350; FloorScore® Certified

Performance Testing

Flexibility	ASTM F 137	Passes
Dimensional Stability	ASTM 2199	Passes
Residual Indentation	ASTM F 970 & ASTM F 1914	Excellent
Flammability	ASTM E 648	Class 1 CRF>0.45
Slip Resistance	ASTM C 1028* ASTM D 2047 ADA Compliant	Very Good (*textures) Passes FTC Slip Resistant Classified Product
Smoke Density	ASTM E 662	<450; Passes
Abrasion	ASTM D 3884	Excellent
Resistance to Heat	ASTM F 1514	Excellent
Color Fastness	ASTM F 1515	Excellent
Chemical Resistance	ASTM F 925	Excellent

Warranty Information

10 year Commercial Limited Wear Warranty

Installation Methods

Unidirectional



UNIDIRECTIONAL

Sizes Available
4" x 36"
6" x 36"
6" x 48"*

Adhesive – CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose), CENTI 2000 EP (Epoxy) or other Tandus Centiva LVT recommended adhesives.

*Excluded from Quickship Express

Product Notes

- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.
- Limited warranty and maintenance information for Tandus Centiva LVT may be found at www.tandus-centiva.com or by dialing 800.248.2878