

FORMATIONS

Through-Body
Porcelain Wall &
Floor Tile

floridatile

FORMATIONS

BY FLORIDA TILE

Formations, a new line by Florida Tile, combines modern style with an impeccable eye for detail. The color pallet lends itself well to a transitional or contemporary decorating style. Formations includes a complete selection of Mosaics, Listellos and Inserts. Formations is so durable, it is ADA compliant and can be used for both residential and commercial settings. See Formations at a dealer or distributor near you or visit us at www.floridatile.com

Porcelain Field Tile

6 x 6



25204 Quartz



25205 Flint



25213 Gravel



25282 Boulder



25296 Dark Pebble

12 x 12



25204 Quartz



25205 Flint



25213 Gravel



25282 Boulder



25296 Dark Pebble

18 x 18



25204 Quartz



25205 Flint



25213 Gravel



25282 Boulder




25296 Dark Pebble

M12



25204/M12 Quartz



25205/M12 Flint



25213/M12 Gravel



25282/M12 Boulder



25296/M12 Dark Pebble

Decorative Mosaics



25204/M2x4 Quartz



25205/M2x4 Flint



25213/M2x4 Gravel



25282/M2x4 Boulder



25296/M2x4 Dark Pebble

Shown on Front: 25213 12x12 Gravel, 2522B/L1.25x12 Geyser Listello Cold



Shown: 25296/M2x4 Dark Pebble, 25296 12x12 Dark Pebble

Listellos, Inserts and Cove Bases



2521B/L1.25x12
Geyser Listello Hot



2522B/L1.25x12
Geyser Listello Cold



2521B/16x6
Geyser Insert Hot



2522B/16x6
Geyser Insert Cold



2520A/L2x12
Lava Listello



25204 Quartz
Cove Base



25205 Flint
Cove Base



25213 Gravel
Cove Base



25282 Boulder
Cove Base



25296 Dark Pebble
Cove Base



25204 Quartz Corner



25205 Flint Corner



25213 Gravel Corner



25282 Boulder Corner



25296 Dark Pebble Corner



Shown: 25205 18x18 Flint

FORMATIONS


BY FLORIDA TILE

Formations Typical Properties ¹ (Floor)	ASTM	ANSI	Results
Coefficient of Friction ²	C-1028	Varies	Dry 0.7
		Varies	Wet 0.6
Durability Classification ³	C1027	N/A	Class IV
Surface Scratch Hardness	Mohs	N/A	7.0 Mohs
Deep Abrasion	N/A	N/A	≤145mm
Break Strength	C-648	250 lbs.	450 lbs.
Water Absorption	C-373	<0.5%	<0.5%
Thickness			9.5mm

¹ These values vary from lot to lot.

² Dry & Wet values from independent test laboratory.

³ Class I Light Traffic Areas, Class II Light Medium Traffic Areas, Class III Medium Heavy Traffic Areas, Class IV Heavy Traffic Areas, Class IV+ Extra Heavy Traffic Areas (High resistance to scratches and stains)



Color Variations

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.

Typical Uses

Formations porcelain tile is ADA compliant and appropriate for all residential and commercial wall and countertop applications, residential and most commercial floor applications.

Field Tile Nominal Size ¹	Metric (cm)	Pcs./Sq Ft ²
6" x 6"	15x15	4
12" x 12"	30x30	1
18" x 18"	45x45	.44

¹ These values may vary from lot to lot.

² These values are based on actual sizes including the grout joint.

Trim Available

Name	Shape	SKU	Nominal Size	Metric (cm)
Bullnose		P43C9	3"x12"	7.5x30
Cove Base		P36C9	6"x12"	15x30
Cove Outside Corner		PB3169	6"x1"	15x2.5
Bullnose		S4669	6"x6"	15x15
Bullnose Outside Corner		SN4669	6"x6"	15x15

¹ These values may vary from lot to lot. ² These values are based on actual sizes including the grout joint.

