



Color shown is 700 Tierra on the floor and backsplash with mosaic in alcove in color 701.

 **Shaw** Tile & Stone™  
shawfloors.com

**La Paz** | ceramic tile

## La Paz

### Features

- Suave and spicy coastal flair: High-tech glazing creates a surface that coordinates with our best-selling hardwood and laminate colors.
- Available with coordinating 6.5" x 6.5" floor tiles, Bullnose, 2" x 2" Mosaics
- Updated color pallet offers muted earth tones as well as contemporary colors

### Colors



100 Azucar




200 Dorado




300 Cactus



500 Blue Agave



600 Chipotle



700 Tierra

### Mosaic



Color  
201



Color  
701

### Tile Sizes

Field Tile	Style
13" x 13"	CS89B
18" x 18"	CS90B
6.5" x 6.5"	CS92B

Trim	Style
3" x 13" Bullnose	CS91B

Accent	Style
13" x 13" Mosaic	CS98B

Technical	Value
Wear Rating Group	4 & 3*
Break Strength	250 lbs.
Water Absorption	7 %
COF (Wet)	.66

\*Wear rating 4, color 100  
 Wear rating 3, all others

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

### Approved Usage

