



 **Shaw** Tile & Stone™



Lucca | *porcelain tile*

Color shown is 700 Noce

shawfloors.com

Lucca

Features

- This durable porcelain tile offers a slip-resistant surface and the visual of cross-cut travertine without the maintenance. The marbled coloration of darker and lighter tones creates a heightened illusion of motion, adding visual excitement.
- Lucca's natural appearance makes it an effortless choice for any space, and multiple sizes—13", 18", 12" x 24", and 2'x2" Mosaic—create countless design options. In particular, the high-trend 12" x 24" rectangle offers flexible design and faster installation. A final selling plus is the Clarity Digital Imaging, which provides outstanding realism.



Colors

- 100 White — creamy shades whirling in very subtle movement, with irregular dark flecks
- 101 Cream — the distressed look of tea-stained linen, sprinkled with occasional darker specks
- 200 Beige — swirls of sandy tones, from sun-bleached to earthy, with random cocoa flecks
- 700 Noce — marbled shades of medium and pale taupe, accented by darker coffee-brown flecks



100 White



101 Cream



200 Beige



700 Noce

Tile Sizes

Field Tile	Style
12" x 24"	CSI2L
18" x 18"	CSI1L
13" x 13"	CSI0L

Trim	Style
3" x 13" Bullnose	CSI5L

Accent	Style
13" x 13" x 2" Mosaic	CSI4L

Technical	
Wear Rating Group	4
Break Strength	407 lbs.
Water Absorption	<.5%
COF (Wet)	.60>

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



Approved Usage

