



Color shown 200 Drift



Color shown 270 Quarry



**Rockwood** | porcelain tile



Color shown 510 Glacier



**Shaw** Tile & Stone™  
shawfloors.com

Color shown 730 Glade

# Rockwood

## Features

A modern linear design and trend-perfect 12 x 24 shape give Rockwood its upscale contemporary flair—while a basketweave 12 x 12 mosaic complements and adds interest to any decor.

The stunning realism of this natural stone visual is due to Clarity Digital Imaging, which creates rich color and beautiful detail. Amazingly durable, this product is freeze-thaw stable and can be installed anywhere—inside, outside, in the basement or on the deck. It may even be used in commercial settings.

### 4 stylish colors:

- **200 Drift**—a beige with warm undertones accented by faint browns
- **270 Quarry**—a light, warm-toned neutral with pale browns creating contrast
- **510 Glacier**—shades of white with striations of pearly grey
- **730 Glade**—earthy, medium wood tones with subtle darker accents

## Colors



200 Drift



270 Quarry



510 Glacier



730 Glade

## Basketweave



200 Drift



270 Quarry



510 Glacier



730 Glade

## Tile Sizes

Field Tile	Style
12" x 24"	CS53L
<b>Accent</b>	
12" x 12" x 2" Mosaic	CS54L
<b>Trim</b>	
3" x 12" Bullnose	CS55L
<b>Technical</b>	
Wear Rating Group	4
Break Strength	300 lbs.
Water Absorption	0.5%
COF (Wet)	>0.60

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



## Approved Usage

