



bosk

Our collection of light commercial luxury vinyl plank, available in a wide range of traditional wood visuals. The ceramic bead finish makes polishing optional and the 12 mil wear layer perform in a variety of applications like offices, salons, assisted living and military housing. Bosk comes in 6" x 48" planks that install quickly and contain 72% recycled content. Leading design and exceeding value make Bosk a go-to line of light commercial luxury vinyl plank.



commercial traffic



Product Specifications

Style Name / Number
Construction
Wear Layer
Wearlayer Thickness
Overall Thickness
Finish
ASTM - F1700
Backing Class

Bosk 5401V
LVT
12 mil
0.012" (0.3mm)
0.098" (2.5mm)
Urethane with Ceramic Bead

Class III Printed Film Vinyl Plank Type A
:Smooth Surface

Packaging

Plank Size
Pieces/Box
Sq Ft / Box
Weight (lb/box)
weight (sq ft)

6" inch width x 48" length
18
35.95
30.42
1.69

Testing

Slip Resistance / ASTM D 2047
Residual Indentation / ASTM F970
Flexibility / ASTM F 137 Passes
Resistance to Heat / ASTM F 1514 Passes
Resistance to Light / ASTM F 1515 Passes
Resistance to Chemicals / ASTM F925 Passes
Radiant Flux / ASTM 648
Smoke Density / ASTM E 662
Dimensional Stability / Federal Standard
501A, method 6211
Resistance to Fungi / ASTM G21
Antibacterial Activity / AATCC 147

>0.60
2000 psi – 0.005 in
Passes
Passes
Passes
Passes
>0.45 watts/cm2, NFPA Class I
Passes < 450
<0.020"/ft
Passes
Passes

Warranty

7-Year Limited Commercial Wear Warranty
(when installed with Shaw 4100 adhesive)

Environmental

Recycled Content
Indoor Air Quality
LEED Scorecard

PC – 39%
PI – 33%
CA 1350 12/1/2010
LEED NC 2.2 & CI 2.0 Rating System & 4.3



P.O. Box 2128
Dalton, GA 30722
800-SHAW-USA (800-742-9872)

value | performance | style | speed



phillyqueencommercial.com

