



bosk pro

Bosk Pro is a diverse assortment of luxury vinyl named for the collection of woods featured in the line. Featuring an enhanced 20-mil wear layer with ceramic bead finish and backed by a 10-year warranty, Bosk Pro is appropriate for use in high-traffic installations. It is manufactured from 72% recycled content and is Floorscore Certified for less environmental impact than competitive LVT products. The Bosk Pro color line mimics wood species from across the world and has a deeply embossed texture for a realistic feel. Our Philadelphia Commercial wood-look flooring installs like a Pro.



commercial traffic



Product Specifications

Style Name / Number
Construction
Wear Layer
Wearlayer Thickness
Overall Thickness
Finish
ASTM - F1700
Backing Class

Bosk Pro 5402V
LVT
20 mil
0.020" (0.5mm)
0.098" (2.5mm)
Urethane with Ceramic Bead

Class III Printed Film Vinyl Plank Type A
:Smooth Surface

Packaging

Plank Size
Pieces/Box
SQFT / Box
Weight (lb/box)
weight (sq ft)

4" inch width x 36" length
36
35.95
30.6
0.85

Testing

Slip Resistance / ASTM D 2047
Residual Indentation / ASTM F970
Flexibility / ASTM F 137 Passes
Resistance to Heat / ASTM F 1514 Passes
Resistance to Light / ASTM F 1515 Passes
Resistance to Chemicals / ASTM F925 Passes
Radiant Flux / ASTM 648
Smoke Density / ASTM E 662
Dimensional Stability / Federal Standard
501A, method 6211
Resistance to Fungi / ASTM G21
Antibacterial Activity / AATCC 147

>0.60
2000 psi – 0.005 in
Passes
Passes
Passes
Passes
>0.45 watts/cm2, NFPA Class I
Passes < 450

<0.020"/ft
Passes
Passes

Warranty

10-Year Limited Commercial Wear Warranty
5-Year Underbed Warranty
(when installed with Shaw 4100 adhesive)

Environmental

Recycled Content

Indoor Air Quality
LEED Scorecard

PC – 39%
PI – 33%
CA 1350 12/1/2010
LEED NC 2.2 & CI 2.0 Rating System & 4.3



P.O. Box 2128
Dalton, GA 30722
800-SHAW-USA (800-742-9872)

value | performance | style | speed



phillyqueencommercial.com

