

VANTAGE II

Engineered wide-plank Xcora® flooring with a High Performance oil finish



FINE BAMBOO FLOORING, PANELS & WORKTOPS

The iconic style of a High-Performance oil finish paired with the beauty and durability of our FSC-certified strand bamboo wear layer over an FSC and CARB II-certified eucalyptus plywood core. Vantage II features both smooth or wirebrushed texture options. A new generation in flooring to create spaces that inspire.



FEATURES + BENEFITS

PERFORMANCE

- Zero-VOC, premium hardwax-oil finish for indoor air-quality, durability, simple maintenance, and superior performance
- Eased edge: almost a square, but with a small bevel for superior edge protection from chipping and wear
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creates a harder, denser, more stable product - 160% harder than oak
- Approved for installation over radiant heat flooring systems

VALUE

- Lifetime structural warranty, Limited Lifetime Residential and Commercial Finish Warranty
- Using eucalyptus as a substrate creates an exceptionally stable product which is also very light, resulting in a floor that combines both the value of superior product engineering and the benefit of the look and durability of Teragren's Xcora strand bamboo

ECOSMART

- Rapidly Renewable FSC Strand Bamboo over FSC® and CARB II certified Eucalyptus Plywood


LEED® CREDITS

- Low Emitting Materials: IEQ 4.3
- Rapidly Renewable Materials: MR6
- Certified Wood: MR7



PRODUCT DETAILS

Nominal Dimensions :	72.83" x 5.59" x 0.55" (1850mm x 142mm x 14mm)
Construction:	Engineered: 3mm strand bamboo over 11mm eucalyptus plywood
Milling:	4 side eased-edge
Profile:	Tongue and Groove
Accessories:	14mm coordinating accessories available
Hardness Rating:	160% harder than oak
Color Variation:	Moderate



INSTALLATION & MAINTENANCE

Installation Environment:	Nail, Staple Glue or Float installation into environments having 35-55% RH.
Nail & Staple Installation:	On or Above grade. Use vapor retarder over wood subfloor.
Glue Installation:	On or Above grade. Use a vapor barrier over cement subfloor OR vapor retarder over wood subfloor.
Float Installation:	On, Above or Below grade. Use a vapor barrier with pad over cement OR vapor retarder with pad over wood subfloor
Recommended Adhesive:	Premium Wood Flooring Adhesive
Nailing Guidelines:	18 gauge cleat or narrow crown staple 11/4" – 11/2"
Acclimation:	Minimum of 48 hours on-site in box
Maintenance:	Rubio Monocoat: Surface Care Soap, Refresh Spray Oil, Maintenance Oil