

# ULTRA MODERN™

COLORBODY™ PORCELAIN

FLOOR



AMERICAN OLEAN®  
PROVEN IN TILE™

AMERICANOLEAN.COM

# ULTRA MODERN™

With a contemporary visual and an appealing commercial color palette, Ultra Modern™ is sure to become a go-to product for large-scale projects requiring a combination of form, function, and cost efficiency. This double-load porcelain tile offers a consistency of visual that most minimalist design schemes demand. TruEdge™ rectification means tighter grout joints while two surface treatments—polished and unpolished—offer design versatility. Six hues ranging from Infinite Cream to Futuristic Black comprise the sophisticated color palette.

Photo features Ultra Modern in Beyond Beige in 24 x 24 Unpolished on the floor.

# ULTRA MODERN™

COLORBODY™ PORCELAIN

## POLISHED

---



INFINITE CREAM UM05



BEYOND BEIGE UM06



PROGRESSIVE GRAY UM07



VISIONARY BROWN UM08



ADVANCED CHARCOAL UM09



FUTURISTIC BLACK UM10

## UNPOLISHED

---



INFINITE CREAM UM05



BEYOND BEIGE UM06



PROGRESSIVE GRAY UM07



VISIONARY BROWN UM08



ADVANCED CHARCOAL UM09




FUTURISTIC BLACK UM10

# ULTRA MODERN™

COLORBODY™ PORCELAIN

## SIZES, SHADE VARIATION & PRICING



**24 x 24 FLOOR TILE**  
(23-5/8" x 23-5/8")  
(60.00 cm x 60.00 cm)



**12 x 24 FLOOR TILE**  
(11-5/8" x 23-5/8")  
(29.70 cm x 60.00 cm)



**MEDIUM**  
(V2)

**TILE THICKNESS:** 3/8"  
**RECOMMENDED GROUT JOINT:** 1/8" (3/16" when multiple sizes are installed in a modular pattern and/or when tile with a length 15" or greater is installed in a staggered brick-joint pattern. Overlap should not exceed 33%)  
**RELATIVE PRICING:** Medium

## TRIM



**BULLNOSE**  
S-43C9  
3 x 12



**COVE BASE**  
S-36C9T  
6 x 12



**COVE OUTCORNER**  
SC-36C9T  
6 x 1

Bullnose, Cove Base and Cove Outcorner trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

## PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOHS	CHEMICAL RESISTANCE
Polished & Unpolished	< 0.5%	> 450 lbs.	8.0	Resistant

### CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

### INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

### SETTING

- Latex modified thin-set
- Epoxy

### GROUTING

- Sanded grout
- Epoxy grout

## FLOOR APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	●*
Wet & Level - Interior	≥ 0.42	●**
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	○
Ramps & Inclines	≥ 0.65	○

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit [americanolean.com/DCOF](http://americanolean.com/DCOF).

\* Polished surface is suitable only for Dry & Level - Interior floor applications.

\*\* Unpolished surface only.

## OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	●
Countertops	●
Pool Linings	○

### APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Cover photo features Ultra Modern Beyond Beige in 24 x 24 Unpolished on the floor.

## NOTES

**SPECIAL INSTALLATION REQUIREMENT:** Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to [americanolean.com/LargeTiles](http://americanolean.com/LargeTiles) for more information.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.



PRE-CONSUMER RECYCLED MATERIALS



TRU-EDGE



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2016 AMERICAN OLEAN (07/16)



AMERICAN OLEAN®  
PROVEN IN TILE™