



CERTIFIED
PORCELAIN
TILE
6.5% to 10% water absorption

castlegate™

PORCELAIN FLOOR
TILE & CERAMIC WALL AND MOSAIC TILE



AMERICAN OLEAN®



Photo features Castlegate, Gray 9 x 12 wall tile and 2 x 2 Universal mosaic on the backsplash.

castlegate™

Inspired by natural stone, Castlegate provides a rustic visual in three warm colors. The porcelain floor tile offered with a coordinating ceramic wall and mosaic tile work beautifully together in both residential and light commercial installations.



FIELD TILE



Beige CG15



Gray CG16



Brown CG17

WALL TILE



Beige CG15



Gray CG16



Brown CG17

DECORATIVE TILE




Universal Mosaic CG18 (Available in blend only)



Photo features Castlegate, Gray 12 x 12 field tile on the floor in a grid pattern.


SIZES, SHADE VARIATION & PRICING



18 x 18 Field Tile
17-3/4" x 17-3/4"
(45.2 cm x 45.2 cm)



12 x 12 Field Tile
11-13/16" x 11-13/16"
(30.0 cm x 30.0 cm)



2 x 2 Mosaic
11-7/8" x 23-7/8" sheet
(30.48 x 60.96 cm sheet)
Dot-mounted



9 x 12 Wall Tile ♦
8-15/16" x 11-15/16"
(22.7 cm x 30.3 cm)

♦ Ceramic body



Tile Thickness: 5/16" Floor and Wall, 1/4" Mosaic

Recommended Grout Joint: 3/16" Floor, 1/16" Wall, 1/8" Mosaic

High
(V3)

Pricing: Low

TRIM



Bullnose
P-4309
3 x 12



Surface Wall Bullnose ♦
S-4309
3 x 9




**Surface Wall Bullnose
Corner** ♦
SN-4309
3 x 3




Surface Mosaic Bullnose ♦
S-886
2 x 2

PATTERN IDEAS





Diamond Pattern
100 pcs. per 100 s/f
12 x 12 100%



Grid Horizontal Pattern

PERFORMANCE CHARACTERISTICS

	D.C.O.F. Wet	C.O.F. Wet Dry		Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance	Abrasion Resistance
 Floor	≥0.42	≥0.60	≥0.70	<0.5%	>275 lbs.	8.0	Resistant	4
Wall	N/A	≥0.50	≥0.80	<20.0%	120-230 lbs.	4.0 - 6.5	Resistant	N/A
 Mosaic	≥0.42	≥0.60	≥0.70	<3.0%	>250 lbs.	8.0	Resistant	4

Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTest™ helps to assess a product's suitability for a commercial environment. For more information, visit www.americanolean.com/DCOF.

FLOOR & MOSAIC APPLICATIONS

	INTERIOR			EXTERIOR	
	RES	LT COM	COM	RES	COM
Floors/Patios: Covered & Uncovered	●	●	●	●	○
Walls/Backsplashes	●	●	●	●	●
Countertops	●	●	●	●	●
Pool Linings	●	●	●	●	●
Pool Decking	○	○	○	○	○

WALL APPLICATIONS

	INTERIOR			EXTERIOR	
	RES	LT COM	COM	RES	COM
Floors/Patios: Covered & Uncovered	○	○	○	○	○
Walls/Backsplashes	●	●	●	●	●
Countertops	●	●	●	●	●
Pool Linings	●	●	●	●	●
Pool Decking	○	○	○	○	○

APPLICATION NOTES:

- Floor tile is suitable for residential exterior floor applications in freezing and non-freezing climates when proper installation methods are followed.
- Wall tile and mosaic tile are suitable for exterior applications in non-freezing climates when proper installation methods are followed.
- Wall tile not recommended for floor applications.
- Use of a latex modified thin-set is recommended for proper installation.
- Not for use on ramps.
- For additional information, refer to Factors to Consider at www.americanolean.com/CommercialFactors.

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for porcelain tile
- Remove cleaning solution with a clean, damp sponge or mop

Installation Methods

Backing Materials

- Concrete
- Mortar bed
- Cementitious backer board

Setting

- Latex modified thin-set
- Epoxy

Floor and Mosaic Grouting

- Sanded grout and sanded cement grout
- Epoxy grout
- Recommended Grout Joint: 3/16" Floor, 1/16" Wall, 1/8" Mosaic

Wall Grouting

- Unsanded grout

NOTES

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.

Since there is shade variation in all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

High variation shading is a part of the natural beauty of this product. To achieve the maximum intended results, tile should be pulled from multiple cartons and placement decided upon prior to installation.

All or select items within this series are Made in the USA, please visit <http://americanolean.com> for more information.



POST CONSUMER
RECYCLED MATERIALS



PRE CONSUMER
RECYCLED MATERIALS



MADE IN
THE U.S.A.
(Floor only)



EXTERIOR
PRODUCT



Certified by UL Environment



Naturally, many of our products can help you earn LEED™ credits. Visit aogreenworks.com for detailed information.

americanolean.com



888-AOT-TILE

© 2013 American Olean (2/13)SSAOCASTLEGATE