



LVT Adhesive Chart

Substrates	Tiles	Planks	Combo Tile & Plank
Concrete			
Good	EW-250	ST-100	ST-100
Best	ST-100	EW-250	EW-250
Plywood			
Good	EW-250	ST-100	ST-100
Best	ST-100	EW-250	EW-250
Radiant Heat			
Good	ST-100	ST-100	ST-100
Best	EW-250	EW-250	EW-250
Existing Vinyl			
Good	N/A	N/A	N/A
Best	ST-100	ST-100	ST-100

ST-100 (Pressure Sensitive) Adhesive

Use: For the installation of Earthwerks solid vinyl plank and tile
Base: Acrylic latex based pressure sensitive
Coverage: 150 - 160 sq ft per gallon
Storage: Non-flammable; protect from freezing
Packaging: Gallon; 4 gallon
Application: 1/16" x 1/16" x 1/16" square notch
Open Time: 15 - 20 minutes for porous substrate
 40 - 60 minutes for non-porous substrates

EW-250 (Hard-Set) Adhesive

Use: For the installation of Earthwerks solid vinyl plank and tile
Base: Hard-setting, water based acrylic
Coverage: 185 - 245 sq ft per gallon
Storage: Non-flammable; protect from freezing
Packaging: Gallon; 4 gallon
Application: 1/32" x 1/16" x 1/32" U notch
Open Time: 15 - 20 minutes *

* Flooring must be installed into wet adhesive

* Do not let the adhesive flash prior to laying the floor