

Brighton

Classification	ASTM F 1700-04 Class III, type B Solid Vinyl Floor Tile
Size	7" x 48" / 177.8 mm x 1219.2 mm
Overall Thickness	1/8" (nominal) / 3.0 mm
Wearlayer	6 mil / 0.15 mm with our exclusive Tuff Shield coating
Construction	Layered plank consisting of wearlayer, film, and backing
Edge	Square
Standard Colors	6 standard colors
Wear Limited Warranty	10-Year Residential
Recycled Content	This product contains a minimum of 50% recycled content. Product can be fully recycled post-use.
Packaging	35 ft ² (3.25 m ²) per carton 15 pieces per carton 60 cartons per pallet 16 pallets per 20' container
Weight Per Carton	37.48 lbs / 17 kg

Please visit www.earthwerks.com for full warranty details and adhesive/application recommendations.

Product Testing

Flammability	ASTM D 2859-06/CPSC FF 1-70	Passed
Critical Radiant Flux	ASTM E 648-06	Class I, CRF ≥0.45
Smoke Density	ASTM E 662-06	<450
Slip Resistance	ASTM C 1028	Exceeds ADA and OSHA recommendations
Static Load Limit	ASTM F 970	1,000 psi



All specifications and offerings subject to change without notice.