

# **FREMONT HICKORY**

engineered





7012 Veranda

# FREMONT HICKORY



Style Number	SW592		
Construction	Epic Plus		
Thickness	Nominal 3/8"		
Width	5"		
Species	Hickory		
Texture	Heavy Scraped		
Gloss Level	20%		
Janka Hardness Rating	2059		
Edge Description	Pilowed		
End Description	Pillowed		
SF per carton	23.66		
SF per pallet	1,419.60		
Installation	Nail, Staple, Glue, Float  Cartons may include random lengths		

#### **Features**

- Beautifully scraped texture accentuates and highlights the natural grain, knots, and rustic character of this hickory hardwood floor
- A strong color palette that lends itself to both classic and contemporary decor

### **Suggested Recommendations**

Style #	Style Name	Coverage	Moisture	<b>Additional Features</b>	
ADHESIVES					
HS105	35MC — Urethane	35 SF / gal for moisture	No Moisture test required	Sound & crack suppressant	
		60 SF / gal as adhesive	Up to 5 lbs. or 85% RH		
111SA	3-in-1 Ultra - MS	35 SF per gal. for moisture	No Moisture test required	Sound & crack suppressant	
		70 SF per gal. as adhesive	Up to 5 lbs. or 85% RH		
HS304	DMC140 — Urethane	35 SF / gal for moisture	No Moisture test required		
SWADH	UreBond Plus	35 SF / gal for moisture	Up to 8 lbs. or 85% RH		
		60 SF / gal	Up to 5 lbs. or 85% RH		

**Trim Pieces** length: 78" (\*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking — but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH38 SORH8
Flush \*Overlap
Reducer Reducer



SSH38 Flush Stairnose



\*Overlap Stairnose



SCH38
Threshold |
Carpet Reducer



**TMH78** T-Molding



QTR96 Quarter Round

## **Benefits**



















