



Color shown 150 Carrara



Color shown 170 Calacatta

Maximus | porcelain tile

Features

Carrara and Calcutta marbles were prized by the ancient Romans as much as we love them today. These are the most popular stones used in the modern kitchen. Combined with pristine white cabinetry and fashionable color schemes, this classic marble stone adds simple elegance to your home.

Colors



170 Calacatta



150 Carrara

Accents

CS17M Wall



170 Calacatta



150 Carrara

CS18M Mosaic



170 Calacatta



150 Carrara

Specifications

| Field Tile | Style |
|------------------------|-------|
| 12" x 12" | CS14M |
| 18" x 18" | CS15M |
| 12" x 24" | CS16M |
| 3" x 6" Wall (ceramic) | CS17M |

| Trim | |
|--------------|-------|
| 3" x 12" SBN | CS19M |

| Accent | |
|-----------------------|-------|
| 12" x 12" x 2" Mosaic | CS18M |

| Technical | |
|-------------------|-----------|
| Wear Rating Group | 4 |
| Break Strength | >300 lbs. |
| Water Absorption | 5% |
| COF (Wet) | >0.70 |
| DCOF | >0.42 |

This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*Ceramic Tiles **OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

