



Color shown is 100 Bella



Color shown is 150 Alfredo



Color shown is 250 Toscana



Color shown is 700 Dorado



# Sophia | porcelain

## Features

This elegant porcelain tile collection is named for the Hagia Sophia—a magnificent museum, originally a Byzantine cathedral, built from a glorious assortment of marble and other stone. Celebrating genius both manmade and natural, Sophia captures the beauty of classic, vein-cut travertine. The collection uses Clarity Digital Imaging design technology to create the much-loved travertine look in a 12" x 24" format, which gives the rich veining and warm colorations the attention they deserve.

Taking nature's genius to a new level, the Sophia series comes in four handsome designer colors: Bella, Alfredo, Toscana, and Dorado. And to complement the stunning large-format tiles, the collection offers 12" x 24" sheet-mounted mosaic strips and 2" x 2" x 12" mosaic sheets. The look of Roman travertine was never more beautifully replicated—an exquisite presentation for well-bred rooms.

## Specifications

<b>Field Tile</b>	
12" x 24"	CS72L
<b>Trim</b>	
3" x 12" Bullnose	CS75L
<b>Accent</b>	
12" x 12" Mosaic	CS73L
12" x 24" Linear Mosaic	CS74L
<b>Technical</b>	
Wear Rating Group	5
Break Strength	407 lbs.
Water Absorption	<.5%
COF (Wet)	0.64
DCOF	0.61
Shade Variation	V2

## Colors



100 Bella

150 Alfredo

250 Toscana

700 Dorado

*This tile features random variations of shade and texture within each carton. To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.*

## Accents



**Mosaic CS73L**

**Linear Mosaic CS74L**

100 Bella

150 Alfredo

250 Toscana

700 Dorado

100 Bella

150 Alfredo

250 Toscana

700 Dorado

\*Ceramic Tiles \*\*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.



## Approved Usage

