

concrete chic™

WITH REVEAL IMAGING™



AMERICAN OLEAN®
FREEDOM OF EXPRESSION™



CERTIFIED
PORCELAIN
TILE
0.5% or less water absorption



PRE-CONSUMER
RECYCLED MATERIALS



MADE IN
THE U.S.A.



REVEAL
IMAGING

concrete chic™

AO's new Concrete Chic refreshes the popular stained cement aesthetic with updated graphics and a contemporary color palette in a product that is made in the USA with recycled content. As at home in modern residential settings as in commercial spaces, Concrete Chic is sure to capture attention.



FLOOR TILE



Current Cream CC65



Trendy Tan CC66



Elegant Gray CC67



Stylish Charcoal CC68



Vogue Brown CC69

SIZES, SHADE VARIATION & PRICING



12 x 24 Floor Tile
(11-13/16" x 23-13/16")
(30.0 cm x 60.48 cm)



12 x 12 Floor Tile
(11-13/16" x 11-13/16")
(30.0 cm x 30.0 cm)



Tile Thickness: 5/16" (12 x 12), 3/8" (12 x 24)
Recommended Grout Joint: 3/16" (Overlap should not exceed 33% when rectangular sizes are used in staggered brick-joint pattern)
Relative Pricing: Medium

TRIM



Bullnose
P-43C9
3 x 12



Cove Base
P-36C9T
6 x 12



Cove Corner
PC-36C9T
1 x 6

Floor bullnose and cove trim are intended to coordinate with floor field tile in the standard 90-degree installation position.

Cove base trim is clay body ceramic and suitable for application in non-freezing climates only.



Photo features Elegant Gray in 12 x 24 on floor.

PERFORMANCE CHARACTERISTICS

	Dynamic C.O.F. Wet	Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance	Abrasion Resistance
Floor	≥ 0.42	< 0.5%	> 275 lbs.	8.0	Resistant	4 (CC65, CC66, CC67) 3 (CC68, CC69)

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.americanolean.com/dcof.

NOTES

Special Installation Requirement: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20 x 20, large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

Installation Methods Backing Materials

- Concrete
- Exterior grade plywood
- Cementitious backer board

Setting

- Latex modified thin-set
- Epoxy

Grouting

- Sanded grout
- Sanded cement grout
- Epoxy grout

APPLICATIONS

	INTERIOR			EXTERIOR	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors/Patios: Covered & Uncovered	●	●	●	●	○
Walls/ Backsplashes	●	●	●	●	●
Countertops	●	●	●	●	●
Pool Linings	●	●	●	●	●
Pool Deckings	○	○	○	○	○

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.



Naturally, many of our products can help you earn LEED™ credits. Visit aogreenworks.com for detailed information.



AMERICAN OLEAN®
FREEDOM OF EXPRESSION™

americanolean.com

888.AOT.TILE