

o mirasol™

GLAZED PORCELAIN FLOOR & MOSAIC TILE
& GLAZED CERAMIC WALL TILE



AMERICAN OLEAN®
FREEDOM OF EXPRESSION™



CERTIFIED
PORCELAIN
TILE

made in the USA

mirasol™

Mirasol is an elegant porcelain floor, mosaic and ceramic wall series with the clean, classic beauty of natural marble. Designs come alive with the incredible color and veining created by Reveal Imaging™ technology. The color palette consists of popular marble looks and colors: Bianco Carrara, Crema Laila and Silver Marble. The floor sizes have a soft matte finish, while the coordinating wall sizes have a glossy finish. Mirasol is an ideal option for those who desire the beauty of marble with the long-lasting durability and ease of maintenance of porcelain tile at a compelling price alternative to natural marble.



Photo features Silver Marble 10 x 14 in grid pattern on the wall and 12 x 24 in grid pattern on the floor.

PORCELAIN FLOOR TILE



Bianco Carrara ML70



Crema Laila ML 71



Silver Marble ML72

PORCELAIN 2 x 4 MOSAIC TILE



Bianco Carrara ML70



Crema Laila ML 71



Silver Marble ML72

*Mosaic tile is mesh-mounted.


CERAMIC WALL TILE



Bianco Carrara ML70




Crema Laila ML 71



Silver Marble ML72

SIZES, SHADE VARIATION & PRICING



24 x 24 Field Tile*
(23-7/16" x 23-7/16")
(59.44 cm x 59.44 cm)



12 x 24 Field Tile*
(11-5/8" x 23-7/16")
(29.56 cm x 59.44 cm)



12 x 12 Field Tile*
(11-1/2" x 11-1/2")
(29.56 cm x 29.56 cm)



2 x 4 Mosaic Brick-joint
(11 7/8" x 11 7/8")
(30.2 cm x 32.6 cm)

*Field tile sizes are modular.



12 x 24 Wall Tile
(11-5/8" x 23-7/16")
(29.56 cm x 59.44 cm)



10 x 14 Wall Tile
(9-27/32" x 13-3/4")
(25 cm x 35 cm)

TRIM



Bullnose
S-43C9
3 x 12



Surface Wall Bullnose
S-43C9
3 x 12



Surface Wall Bullnose
S-4310
3 x 10



Surface Wall Bullnose Outcorner
SN-4310
3 x 3



Tile Thickness: 3/8"


Recommended Grout Joint: 1/16" 10 x 14 Wall; 1/8" 12 x 24 Wall, Floor and Mosaic (3/16" when rectangular sizes are used in a staggered brick-joint pattern, or when multiple sizes are used in a modular pattern, overlap not to exceed 33%)

Pricing: Medium


High
(V3)




Photo features Silver Marble in 10 x 14 on tub and wall.



Hopscotch
20 pcs. per 100 s/f
24 x 24 80%
12 x 12 20%



Corridor
17 pcs. per 100 s/f
24 x 24 67%
12 x 24 33%



Herringbone
50 pcs. per 100 s/f
12 x 24 100%

Dark lines indicate repeat.

PERFORMANCE CHARACTERISTICS

	Dynamic C.O.F. Wet			Static C.O.F. Wet Dry		Moisture Absorption	Breaking Strength	MOH's	Chemical Resistance	Abrasion Resistance
Floor & Mosaic	≥ 0.42	≥ 0.60	≥ 0.70	< 0.5%	325 lbs.	8.0	Resistant	3 - 4		
Wall	--	--	--	< 20.0%	>120 lbs.	4.0 - 6.5	Resistant	--		

Dynamic C.O.F. (Wet) value as measured by the DCOF AcuTestSM helps to assess a products suitability for a commercial environment. For more information, visit our website at www.americanolean.com/DCOF.

Cleaning Procedures

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for porcelain tile
- Remove cleaning solution with a clean, damp sponge or mop

Installation Methods Backing Materials

- Concrete
- Exterior grade plywood
- Cementitious backer board

Setting

- Latex modified dry-set mortar
- Epoxy

Grouting

- Sanded grout (floor)
- Epoxy grout
- Unsanded grout (wall)

FLOOR & MOSAIC APPLICATIONS

	INTERIOR			EXTERIOR	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors/Patios: Covered & Uncovered	●	●	●	●	○
Walls/Backsplashes	●	●	●	●	●
Countertops	●	●	●	●	●
Pool Linings	●	●	●	●	●
Pool Deckings	○	○	○	○	○

Floor tile is suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

WALL APPLICATIONS

	INTERIOR			EXTERIOR	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors/Patios: Covered & Uncovered	○	○	○	○	○
Walls/Backsplashes	●	●	●	●	●
Countertops	●	●	●	●	●
Pool Linings	●	●	●	●	●
Pool Deckings	○	○	○	○	○

Wall tile is suitable for exterior walls in non-freezing climates only.

NOTES

Special Installation Requirement: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20 x 20, large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Use of a latex modified thin-set is recommended for proper installation.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.

For additional information on Test Results and Classifications, visit us at www.daltile.com/TestResults

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.



PRE-CONSUMER RECYCLED MATERIALS



REVEAL IMAGING



TRU-EDGE



EXTERIOR PRODUCT



Naturally, many of our products can help you earn LEEDTM credits. Visit aogreenworks.com for detailed information.



AMERICAN OLEAN[®]
FREEDOM OF EXPRESSION[™]

americanolean.com

888.AOT.TILE