

HISTORIC BRIDGE™

WITH REVEAL IMAGING™

PORCELAIN



AMERICAN OLEAN®
PROVEN IN TILE™

AMERICANOLEAN.COM

HISTORIC BRIDGE™

Historic Bridge perfectly captures the look of exposed and weathered wood, with authentic details like water staining and cracking to worn-paint effects. Four rich colors feature a high level of variance. Special glazing adds to the genuine effect by creating a slight sheen along the graining. All colors are available in a plank size well-suited for creating floors with a rustic look. Historic Bridge answers current demand for organic influences from residential to commercial settings.

Photo features Upper Ferry in 6 x 36 on the floor.

FLOOR TILE



UPPER FERRY HB01



OLD HOLLOW HB02



BANK'S BRIDGE HB03



OLD FORGE HB04

SIZES, SHADE VARIATION & PRICING



6 x 36 FLOOR TILE
(5-7/8" x 35-7/16")
(15 cm x 90 cm)



RANDOM
(V4)

TILE THICKNESS: 5/16"
RECOMMENDED GROUT JOINT: 3/16" (when rectangular size is used in a staggered brick-joint pattern, the overlap should not exceed 33%)
RELATIVE PRICING: Medium to High

TRIM



BULLNOSE
S-43H9
3 x 18

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

FLOOR APPLICATIONS

	TARGET DCOF WET	SUITABLE
Dry & Level - Interior	N/A	
Wet & Level - Interior	≥ 0.42	
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	≥ 0.60	
Ramps & Inclines	≥ 0.65	

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1-2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.americanolean.com/dcof.

OTHER APPLICATIONS

	SUITABLE
Walls/Backsplashes	
Countertops	
Pool Linings	

APPLICATION NOTES:

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOH'S	CHEMICAL RESISTANCE	ABRASION RESISTANCE
Floor	< 0.5%	> 275 lbs.	8.0	Resistant	3

CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge
- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

INSTALLATION METHODS BACKING MATERIALS

- Concrete
- Exterior grade plywood
- Cementitious backer board

SETTING

- Latex modified thin-set
- Epoxy

GROUTING

- Sanded grout
- Sanded cement grout
- Epoxy grout

NOTES

SPECIAL INSTALLATION REQUIREMENT: For proper bonding, medium bed mortar should be utilized in installing tiles with a dimensional length size greater than 20 x 20, large rectangles or tiles with greater dimensional thickness than normal. Back buttering tiles of this nature in the installation process will also assure proper coverage for bonding.

Since there is shade variation in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information, refer to "Factors to Consider" at <http://americanolean.com/factors-to-consider.cfm>.



PRE CONSUMER RECYCLED MATERIALS



MADE IN THE U.S.A.



REVEAL IMAGING

PROVEN PORCELAIN TILE



Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE

©2015 AMERICAN OLEAN (04/15)
ASSEMBLED IN MEXICO



AMERICAN OLEAN®
PROVEN IN TILE™