



FLOOR

SADDLE BROOK™

GLAZED PORCELAIN with Reveal Imaging™

 **daltile**®
IMAGINE WHAT'S POSSIBLE



Above and cover photos feature Farmhouse in 6 x 36 field tile.

The Beautiful Look of Hardwood without Compromise

Let the warmth and timeless look of hardwood flow through the entire home with Saddle Brook glazed porcelain tile. An authentic hardwood visual is combined with four natural wood tones to give a realistic look on a durable, scratch-resistant surface.

- **AUTHENTIC APPEAL**
 - Timeless design and a warm color palette are combined for an authentic look
 - Reveal Imaging™ technology creates an incredibly authentic visual by combining rich color with a wide variation of natural wood patterns
 - Popular plank size with coordinating trim
- **RICHNESS OF WOOD WITHOUT THE WORRY**
 - High moisture resistance, which is ideal to bring a wood look to areas such as bathrooms and kitchens
 - Ease of maintenance and high durability of glazed porcelain

 **PRE CONSUMER RECYCLED MATERIALS**

 **MADE IN THE U.S.A.**

 **REVEAL IMAGING™**

All or select items within this series are made in the USA. For more information, visit daltile.com/SaddleBrook.

 **CERTIFIED PORCELAIN TILE**
0.9% or less water absorption

FIELD TILE



Oak Trail SD13



Farmhouse SD14



Walnut Creek SD15




Gravel Road SD16

SADDLE BROOK™

GLAZED PORCELAIN with Reveal Imaging™

SIZES

			Thickness	Sq. Ft. per Carton	Pieces Per Carton
	6 x 36 Field Tile	(5-7/8" x 35-7/16") (15.00 cm x 90.00 cm)	5/16"	14.50	10

FLOOR APPLICATIONS

	Target DCOF wet	Tile Texture or Added Abrasive	Suitable
Dry & Level – Interior	N/A	N/A	✓
Wet & Level – Interior	≥ 0.42	Optional	✓
Commercial Dining Areas – Interior	≥ 0.50	Optional	
Pool Decking & other wet areas with minimal footwear	≥ 0.55	Required if tile size is > 3 x 3	
Covered Exterior	≥ 0.60	Required if tile size is > 3 x 3	
Interior Ramps, Incline and Uncovered Exterior	≥ 0.65	Required if tile size is > 6 x 6	


A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A1371–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™, visit www.daltile.com/dcof.

OTHER APPLICATIONS

	Suitable
Walls/Backsplashes	✓
Countertops	✓
Pool Linings	


Floor tile suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces Per Carton
 Bullnose	S-43H9	3 x 18	16

Floor bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" (overlap should not exceed 33% when installing rectangular size in a staggered brick-joint pattern)	 High (V3)

TEST RESULTS

	ASTM#	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 275 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	3

For additional information, visit daltile.com/information/TestResults.

NOTES

Special consideration needs to be given when installing tiles 20" and larger. Please refer to <http://daltile.com/LargeTiles> for more information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at daltile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDITS. For more detailed information, visit daltilegreenworks.com.



SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GET.DAL TILE.COM



7834 C. F. Hawn Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE

©2015 Dal-Tile Corporation (4/15)